



cantechtape.com

103-00



ECONOMY INDUSTRIAL MASKING TAPE

DESCRIPTION

This tape is made of crepe paper backing coated with a natural rubber adhesive. Designed for non-critical masking application, bundling, labeling and holding.

MAIN FEATURES

- Good balance between paper and adhesive.
- Thin crepe paper providing good tensile and elongation.
- Excellent natural rubber adhesive delivering good initial tack and holding power.
- Temperature resistance of 80°C (176°F) for 30 minutes.
- Smooth unwind and easily hand-tearable.

APPLICATIONS

- For short term non-critical applications.
- Excellent “Production” tape.
- Holding and bundling.
- Designed for indoor application.

TECHNICAL DATA

| | |
|------------------------------|-----------------------------|
| Colour | Natural |
| Backing | Crepe Paper |
| Adhesive | Solvent Base Natural Rubber |
| Thickness | 5.0 mils |
| Adhesion to steel | 26 oz/in |
| Tensile strength | 18 lbs./in |
| Elongation..... | 12% |
| Application Temperature..... | 15°C (60°F) TO 40°C (105°F) |
| Temperature Resistance | 70°C (158°F) for 30 minutes |

STOCK SIZE

- 12mm x 55m – 72 rolls/case
- 18mm x 55m – 48 rolls/case
- 24mm x 55m – 36 rolls/case
- 36mm x 55m – 24 rolls/case
- 48mm x 55m – 24 rolls/case
- 72mm x 55m – 12 rolls/case

NATURAL RUBBER ADHESIVE

INDUSTRIAL QUALITY

Please note:

Specifications quoted are averages only and may vary within industry tolerances.

The final user must assure product suitability for the application and assumes all risks and liabilities

Canadian Technical Tape Ltd 455 Côte Vertu, Montreal, QC H4N 1E8 Tel.: 514.334.1510 Fax: 514.334.1183 Toll Free: 1.800.334.1567

Cantech Industries, Inc. 2222 Eddie Williams Road, Johnson City, TN 37601 Tel.: 423.928.8331 Fax: 423.928.0311 Toll Free: 1.800.654.3947